

TESCON NAIDECK

Double-sided nail sealing tape



Technical data

		Substance
Material		Butyl rubber
Release film		siliconized paper
Attribute	Regulation	Value
Colour		black
Thickness		1.0 mm
Exposure time		6 months, installed under the counter battens
Application temperature		5 °C to 35 °C ; 41 °F to 95 °F
Temperature resistance		permanent -40 °C to 80 °C ; -40 °F to 176 °F
Storage		cool and dry

Area of application

Nail sealing tape under counter battens for sloped roof structures.

In accordance with the Central Association of the German Roofing Trade (ZVDH), the use of nail sealing tapes in combination with "underlays/ sarking membranes with seam and perforation protection" (SOLITEX connect variants) is a required additional measure in the case of "more demanding requirements" (e.g. if the roof pitch is less than the standard roof pitch).

If required, TESCO NAIDECK also serves as a suitable additional measure to create a temporary covering.

Forms of delivery

Art. no.	GTIN	Length	Width	Weight	Sales unit	Container
11737	4026639117373	20 m	50 mm	1.35 kg	6	576
11943	4026639119438	20 m	50 mm	33 kg	1	24
1AR00900	4026639209009	20 m	75 mm	33 kg	1	24

Advantages

- ✓ Very good sealing effect: sealing material is pulled into the hole created when a nail or screw is fitted
- ✓ Conforms to regulations: satisfies the requirements of ZVDH and of SIA 232/1
- ✓ Reliable during the construction phase: suitable for temporary coverings / sealing during construction work

Substrates

Clean subsurfaces before sticking.

Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded. Subsurfaces must be sufficiently dry and stable.

Lasting nail-tightness is achieved on all pro clima exterior membranes and other underlay/sarking and wall lining membranes (e.g. those made of PP and PET) as well as MDF board and softwood fibre sub-roof panels.

The best results in terms of structural stability are achieved on high-quality subsurfaces.

It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases.

Pretreatment with TESCO PRIMER is recommended in the case of subsurfaces with insufficient stability.

General conditions

Perforation seals will only be effective on roof lining, underlay or sarking membranes that have been installed with no folds or creases.

Install TESCO NAIDECK with no interruptions between the counter battens and the roof lining membrane. This ensures that perforations that may arise when the roof battens are being fastened will also be sealed.

Adhesion can be carried out to the counter batten or to the subsurface that is to be sealed. Press firmly to secure the tape in place.

Daytime and nighttime temperatures must be >5 °C / >41 °F when working with this product.

