

## INSTAABOX

Installation box



### Technical data

Substance		
Material	polyethylene, flexible and extensible	
Attribute	Regulation	Value
Colour		translucent
Length / width installation space/cavern		260 mm / 130 mm
Length / width over all		320 mm / 190 mm
Depth		55 mm
Cable diameter		max. 20 mm
sd-value	BS EN 1931	> 10 m
g-value		> 50 MNs/g
Fire rating	BS EN 13501-1	E
Temperature resistance		permanent -10 °C to 80 °C ; 14 °F to 176 °F
Storage		cool and dry

### Application

For structures without dry lining, the INSTAABOX can create space for junction boxes and the like. It is attached and sealed so that it is airtight to the existing vapour retarding and airtightness layer.

It complies with the requirements of DIN 4108-7, SIA 180 and RT 2012 with regard to airtightness when using conventional junction boxes. The INSTAABOX can be used for both internal and external walls.

The INSTAABOX is oversized to prevent the airtight sealing layer being damaged if holes need to be drilled for the junction boxes.

### Forms of delivery

Art. no.	GTIN	Length	Width	Contents	Weight
1AR02160	4026639221605	320 mm	190 mm	10 pieces	0.26 kg

### Advantages

- ✓ For cables and conduits up to 20 mm in diameter
- ✓ Construction in adherence with standards: for airtight bonding in accordance with DIN 4108-7, SIA 180 and RT 2012
- ✓ Provides space for up to three junction boxes
- ✓ Can be extended at will by cutting and sticking together again
- ✓ Excellent values in the hazardous substance test, has been tested according to the ISO 16000 evaluation scheme

### Substrates

The INSTAABOX can be used on all common airtight substrates used in construction. Recommendations on suitable sealants for connecting it to the airtight sealing layer (e.g. vapour retarder, wood-based panels or mineral substrate) is given in the pro clima application matrix.

Further information can be found in the technical data sheets provided with the sealant.

### General conditions

The bonds should not be subjected to tensile strain.

When the vapour control membrane is sealed, the weight of the insulating material must be borne by lathing. Adhesion should be supported by additional laths, if necessary.

Press firmly to secure the adhesive tapes in place. Ensure that there is sufficient resistance pressure.

Airtight seals can only be achieved on vapour control membranes that have been laid without folds or creases.

Ventilate continuously and systematically to prevent build-up of excessive humidity; use a dryer if necessary.



# Tŷ-Mawr

Caring for the future,  
respecting the past...

Manufacturer and supplier of traditional and environmentally-friendly building materials.

Tested for hazardous  
substances according to



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

**Sales & Distribution** - Tŷ-Mawr Lime Ltd, Unit 12, Brecon Enterprise Park, Brecon, Powys. LD3 8BT. - **Tel** : 01874 611 350  
**Manufacturing & Courses** - Tŷ-Mawr Lime Ltd, Ty-Mawr, Llangasty, Brecon, Powys, LD3 7PJ. - **Email**: [tymawr@lime.org.uk](mailto:tymawr@lime.org.uk)