



Tŷ-Mawr Caring for the future, respecting the past...

Manufacturer and supplier of traditional and environmentally-friendly building materials



Tradiblanc® HL 5

THE WHITE LIME



THE + BENEFITS

- Respects the colour of the local sands
- High yield
- Quick setting
- Resistant

SUITABLE FOR

Bedding and pointing mortars, stipple and base coats, limecrete, above the roof line, chimneys, lime screed, floor tiling. Before starting, always try on a small test area.

PACKAGING

25kg bag 40 bags per pallet (1T pallet)

PRODUCT COMPOSITION

Based on Saint-Astier[®] Natural Hydraulic Lime with addition of OPC and additives.

SHELF LIFE & GUARANTEE

One year from production date if protected in the original packaging and stored in dry conditions. Manufacturer Civil Responsibility.

Sales & Distribution - Tŷ-Mawr Lime Ltd, Unit 12, Brecon Enterprise Park, Brecon, Powys. LD3 8BT. - Tel : 01874 611 350 Manufacturing & Courses - Tŷ-Mawr Lime Ltd, Ty-Mawr, Llangasty, Brecon, Powys, LD3 7PJ. - Email: tymawr@lime.org.uk





Tŷ-Mawr Caring for the future, respecting the past...

Manufacturer and supplier of traditional and environmentally-friendly building materials

Tradiblanc® HL 5



PERFORMANCE

| ESSENTIAL SPECIFICATION | MORTAR (sand 0–3mm, volume 1:3) | TEST STANDARDS |
|---|---|-------------------|
| Dry density | 1425g.l +/- 25g dry | EN 1015-11 |
| Workability | 210mm (+/- 10%) | EN 1015-3 |
| Water retention | 81% (+/- 3%) | CSTB |
| Compressive strength at 24 hours 7 days 28 days | 1.5 N.mm ² 4-5 N.mm ² 6-7 N.mm ² | BS 998.2 |
| Thermal conductivity | 0.540 W/m.K | EN 1745 |
| Vapour permeability | 1,60.10-9 kg/m2sPa (0.77g x m2 x h x mmHg) | EN 1015-19 |
| Elasticity moduli | 7000 – 9000 MPa | CSTB |
| Capillarity | 0.75 g.min. | EN 1015 |
| Fire resistance | Class A1 (with silica or calcareous sands) | |

APPLICATION

Application by spray gun possible.

WORKING TEMPERATURE

Not below 8°C or above 30°C. Ensure high suction substrates are thoroughly dampened before application. Avoid rapid drying due to high temperatures and strong winds by covering and curing with a light water mist as necessary. Reseal open bags as soon as possible.

PREPARATION

Up to 5 minutes in conventional drum mixers.

HEALTH & SAFETY

Follow the instructions on the safety data sheet and wear the appropriate equipment (gloves, mask, safety shoes...).

FURTHER INFORMATION

Available on our website following this <u>link</u>.





June 2023

Sales & Distribution - Tŷ-Mawr Lime Ltd, Unit 12, Brecon Enterprise Park, Brecon, Powys. LD3 8BT. - Tel : 01874 611350 Manufacturing & Courses - Tŷ-Mawr Lime Ltd, Ty-Mawr, Llangasty, Brecon, Powys, LD3 7PJ. - Email: tymawr@lime.org.uk