



**Ty-Mawr Purpose General Filler is a non-shrink, ready mixed mortar made with natural hydraulic lime, siliceous and calcareous sand (0-0.6mm) and additives. Suitable for repairing or restoring cement renders, lime plasters and refurbishment work on composite backgrounds.**

## Instructions for Use

- The surfaces should be clean and grease-free. Any loose material should be brushed off.
- Moisten highly absorbent surfaces with water prior to application.
- 1 kg of Filler should be vigorously mixed with 200-250 ml water until a lump free paste is obtained.
- Apply filler to create an even surface. Do not apply in layers greater than 20mm. If necessary level-out deep holes and cracks a second time.
- Fine cracks will need to be opened up to a width of at least 5mm before filling.
- Use the filler within 4 hours, do not rework.
- If you are unsure about the appropriateness of this product for your specific application then please contact Ty-Mawr.

**Water addition:** 200 to 250ml per 1 kg.

**Consumption:** 1.7kg per mm of thickness per m<sup>2</sup>.

**Shelf life:** 12 months if kept in dry storage conditions.

**Granulometries:** 0-0.6mm.

## Health and Safety Information



### Warning

**Skin Irritation 2 H315** - Causes skin irritation  
**STOT SE 3 H335** - May cause respiratory problems



### Danger

**Eye Damage 1 H318** - Causes serious eye damage

### Precautionary Statements

**P102** Keep out of reach of children

**P280** Wear protective gloves, eye protection/face mask.

**P305 + P351 + P310** If in eyes rinse cautiously with water for several minutes and immediately get medical assistance.

**P352 + P352** If on skin, wash affected area part immediately with plenty of soap and water.